

2011 SKANDIC® SWT



PACKAGE HIGHLIGHTS

- Yeti™ II platform
- 24 x 156 x 1.25-inch track
- Synchromesh transmission with reverse (2-1-N-R)
- Electric start
- High windshield with mirrors
- Lynx Telescopic front suspension
- Mountain strap
- 12V power outlet
- 2-up seat with backrest, underseat storage
- Cargo rack
- Hitch
- Analog gauge

ENGINE CHOICE

Engine	Rotax® V-800
Engine details	Liquid-cooled, four-stroke
Cylinders	2
Displacement	799.9 cc / 48.8 in ³
Bore	91 mm / 3.6 in
Stroke	61.5 mm / 2.4 in
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Regular unleaded
Minimum octane	87
Fuel tank	42 liters / 11.1 gallons
Oil tank capacity	2.2 liters / 2.3 quarts
Exhaust system	Double head-pipe, baffle muffler

POWERTRAIN

Drive clutch type	TRA™ IV
Driven clutch type	NDT 6K VSA
Engagement	2500 RPM
Small sprocket number of teeth	1 st gear = 3.23:1 ratio
Large sprocket number of teeth	2 nd gear = 1.98:1 ratio
Drive sprocket number of teeth	8
Drive sprocket diameter	158.7 mm / 6.2 in
Brake system	Hydraulic

DRY WEIGHT

326 kg / 717 lb

FEATURES

Frame	Yeti II	Electric start	Standard	Fuel gauge	Mechanical
Skis	Adjustable with liner	Reverse	Mechanical	Temperature gauge	Optional
Seating	2-up modular with underseat storage	Heated throttle lever	Standard	Mirrors	Standard
Backrest	Standard	Heated grips	Standard	Windshield	High
Handlebar	Straight with mountain strap	Speedometer	Standard	Carbide runner	Standard
		Tachometer	Optional	Hitch	Tongue type

COLOR CHOICE

Yellow / Black

DIMENSIONS

Vehicle overall length	3070 mm / 120.9 in
Vehicle overall width	1155 mm / 45.5 in
Vehicle overall height	1355 mm / 53.3 in
Ski stance	900 mm / 35.4 in
Ski overall length	1112 mm / 43.8 in
Ski width	250 mm / 9.8 in
Track nominal width	600 mm / 24 in
Track nominal length	3968 mm / 156 in
Track profile height	31.8 mm / 1.25 in

SUSPENSION

Front suspension	LTS
Front shock	Hydraulic
Front suspension max. travel	150 mm / 6 in
Rear suspension	Easy ride XWLS
Center shock	Hydraulic
Rear shock	Hydraulic
Rear suspension max. travel	215 mm / 8.5 in